



SINGLE DISC SWING CHECK VALVE

Model: C04.0202



SPECIFICATION

DESIGN

Compact Structure and right Weight BS EN12334: 2001

PRESSURE RATING

16 Bar

WORKING TEMPERATURE

-15°C~120°C

OPERATOR

Testing: According to BS EN 12266-1

CONNECTION

Water Connection According to PN10/PN16, BS EN 1092-2

MATERIAL

Parts	Materials	Parts	Materials
Coating	Fusion Bonded Epoxy	Disc	Nickel Plated Ductile Iron
Body	Cast Iron		Stainless Steel
	Ductile Iron		Aluminum Bronze
Sealing	EPDM/NBR	Stem	Stainless Steel
Spring	Stainless Steel		

DIMENSION

Size DN		L	øE	Ø	
(mm)	(inch)			DIN2501/BS4504	
				PN10	PN16
50	2"	44.5	33	107	
65	2.5"	47.6	43	127	
80	3"	50.8	52	142	
100	4"	57.2	74	162	
125	5"	63.5	95	192	
150	6"	69.9	118	218	
200	8"	73	163	273	
250	10"	79.4	194	328	329
300	12"	85.7	238	378	384
350	14"	108	266	428	446
400	16"	108	318	489	498

